



#### Product Advantages

Energy saving up to 80% compared to conventional lighting fixtures
High efficiency LED light system
Long life, high quality LED and high efficiency driver
For corrosion resistance, zincoprim applied to surface of the luminaire before electrostatic powder coating
Inox bolts
High quality silicone gasket provides sealing

#### Product Specifications

Housing:	Aluminum die-cast housing
Optical Cover:	Tempered glass
Light Source:	Mid Power LED
Ingress Protection Rating:	IP65
Electrical Protection Class:	Class 1
Diameter (a):	400 mm
Height (h):	170 mm
Working Temperature:	-25 °C ~ +50 °C

#### Electrical Properties

Nominal Power:	175 W
Operating Mode:	Compatible LED Driver
Input Voltage:	220 - 240 VAC
Input Frequency:	50 - 60 Hz
Power Factor:	> 0.90
Current:	718 mA
Total Harmonic Distortion:	< 15 %
Control Type:	On - Off Controller

#### Photometric Properties

Color Temperature:	3000 °K - 4000 °K - 6500 °K
Luminous Flux:	20475 lm - 22522 lm - 22750 lm
Luminous Flux Tolerance:	< 10 %
Efficacy:	130 lm/W
Colour Rendering Index (CRI):	≥ 80
Beam Angle:	60° - 90° - 120°