



### Product Advantages

Energy saving up to 80% compared to conventional lighting fixtures
High efficiency LED light system
Long life, high quality LED and high efficiency driver
For corrosion resistance, zincoprim applied to surface of the luminaire before electrostatic powder coating
Inox bolts
High quality silicone gasket provides sealing

### Product Specifications

Housing:	Aluminum die cast housing, chrome front frame, aluminum pressed recessed box
Optical Cover:	Tempered glass
Light Source:	High Power LED
Ingress Protection Rating:	IP67
Electrical Protection Class:	Class 1
Inner Diameter (a):	50 mm
Outer Diameter (b):	70 mm
Height (c):	105 mm
Working Temperature:	-20 °C ~ +50 °C

### Electrical Properties

Nominal Power:	3 W
Operating Mode:	Compatible LED Driver
Input Voltage:	220 - 240 VAC
Input Frequency:	50 - 60 Hz
Power Factor:	> 0.90
Current:	14 mA
Total Harmonic Distortion:	< 15 %
Control Type:	On - Off Controller

### Photometric Properties

Color Temperature:	3000 °K - 4000 °K - 6500 °K
Luminous Flux:	351 lm - 408 lm - 441 lm
Luminous Flux Tolerance:	< 10 %
Efficacy:	147 lm/W
Colour Rendering Index (CRI):	≥ 80
Beam Angle:	15° - 25°