



Product Advantages

Energy saving up to 80% compared to conventional lighting fixtures
High efficiency LED light system
Long life, high quality LED and high efficiency driver
For corrosion resistance, zincoprim applied to surface of the luminaire before electrostatic powder coating
Inox bolts
High quality silicone gasket provides sealing

Product Specifications

Housing:	Aluminum die cast housing, chrome front frame, aluminum recessed box
Optical Cover:	Tempered glass
Light Source:	High Power LED
Ingress Protection Rating:	IP67
Electrical Protection Class:	Class 1
Inner Dimentions (a):	100 mm
Outer Dimentions (b):	110 mm
Height (c):	135 mm
Working Temperature:	-20 °C ~ +50 °C

Electrical Properties

Nominal Power:	5 W
Operating Mode:	Compatible LED Driver
Input Voltage:	220 - 240 VAC
Input Frequency:	50 - 60 Hz
Power Factor:	> 0.90
Current:	22 mA
Total Harmonic Distortion:	< 15 %
Control Type:	On - Off Controller

Photometric Properties

Color Temperature:	3000 °K - 4000 °K - 6500 °K
Luminous Flux:	474 lm - 529 lm - 595 lm
Luminous Flux Tolerance:	< 10 %
Efficacy:	119 lm/W
Colour Rendering Index (CRI):	≥ 80
Beam Angle:	30° - 50°