NARLIGHT

Rectangle In Ground Luminaire

LGA1020 · JUNIPERUS

I (E 🔣 Kons 🐵



d

b

e

Product Advantages		
Energy saving up to 80% compared to conventional lighting fixtures		
High efficiency LED light system		
Long life, high quality LED and high efficiency driver		
For corrosion resistance, zincoprim applied to surface of the luminaire before electrostatic powder coating		
Inox bolts		
High quality silicone gasket provides sealing		

Product Specifications Housing: Aluminum profile and die cast housing, aluminum pressed recessed box Tempered glass / Transparent PMMA Optical Cover: Light Source: High Power LED Ingress Protection Rating: IP67 Electrical Protection Class: Class 1 Inner Dimensions (a × b): 68 × 688 mm Outer Dimensions (c × d): 75 × 690 mm Height (e): 75 mm Working Temperature: -20 °C ~ +50 °C

	Electrical Properties
Iominal Power:	32 W
Operating Mode:	Compatible LED Driver
Input Voltage:	220 - 240 VAC
Input Frequency:	50 - 60 Hz
Power Factor:	> 0.90
Current:	153 mA
Total Harmonic Distortion:	< 15 %
Control Type:	On - Off Controller

Photometric Properties		
Color Temperature:	3000 °K - 4000 °K - 6500 °K	
Luminous Flux:	3159 lm - 3402 lm - 3968 lm	
Luminous Flux Tolerance:	< 10 %	
Efficacy:	124 lm/W	
Colour Rendering Index (CRI):	≥80	
Beam Angle:	10° - 24° - 36°	



Narlight Aydinlatma San. ve Tic. A.S. • www.narlight.com.tr • Specifications of this product are subject to change without prior notice. The picture may not reflect the actual product. Document no: 2709211649