



Product Advantages	
Energy saving up to 80% compared to conventional lighting fixtures	
High efficiency LED light system	
Long life, high quality LED and high efficiency driver	
Inox bolts	
High quality silicone gasket provides sealing	

Product Specifications	
Housing:	Aluminum extrusion housing
Optical Cover:	PMMA diffuser
Light Source:	High Power LED
Ingress Protection Rating:	IP66
Electrical Protection Class:	Class 1
Width (a):	67 mm
Length (b):	610 mm
Height (c):	35 mm
Working Temperature:	-20 °C - +50 °C

Electrical Properties		
Nominal Power:	30 W	30 W
Operating Mode:	Compatible LED Driver	Compatible LED Driver
Input Voltage:	220 - 240 VAC	220 - 240 VAC
Input Frequency:	50 - 60 Hz	-
Power Factor:	> 0.90	-
Current:	143 mA	143 mA
Total Harmonic Distortion:	< 15 %	-
Control Type:	DALI / On - Off Controller	PWM / DMX

Photometric Properties		
Color Temperature:	3000 °K - 4000 °K - 6500 °K	RGB - WA
Luminous Flux:	2970 lm - 3266 lm - 3300 lm	-
Luminous Flux Tolerance:	< 10 %	-
Efficacy:	110 lm/W	-
Colour Rendering Index (CRI):	≥ 80	-
Beam Angle:	15° - 30° - 45° - 60°	15° - 30° - 45° - 60°