



#### Product Advantages

Energy saving up to 80% compared to conventional lighting fixtures
High efficiency LED light system
Long life, high quality LED and high efficiency driver
For corrosion resistance, zincoprism applied to surface of the luminaire before electrostatic powder coating
Inox bolts
High quality silicone gasket provides sealing

#### Product Specifications

Housing:	DKP sheet housing
Optical Cover:	Tempered glass
Light Source:	Mid Power LED
Ingress Protection Rating:	IP65
Electrical Protection Class:	Class 1
Inner Dimensions (a):	171 mm
Outer Dimensions (b x b):	195 x 195 mm
Height (c):	85 mm
Working Temperature:	-20 °C ~ +50 °C

#### Electrical Properties

Nominal Power:	11 W
Operating Mode:	Compatible LED Driver
Input Voltage:	220 - 240 VAC
Input Frequency:	50 - 60 Hz
Power Factor:	> 0.90
Current:	55 mA
Total Harmonic Distortion:	< 15 %
Control Type:	On - Off Controller

#### Photometric Properties

Color Temperature:	3000 °K - 4000 °K - 6500 °K
Luminous Flux:	953 lm - 1044 lm - 1100 lm
Luminous Flux Tolerance:	< 10 %
Efficacy:	100 lm/W
Colour Rendering Index (CRI):	≥ 80